EKO-TRADING CO., LIMITED

Water Filters

NW water filters

This series water filter is made of AS, PP or PET. They are suitable for the family, hotel and restaurant use. You can choose proper filter cartridge according to local water quality. Proper filter cartridge can remove odor, smell, color and even organic chemicals from tap water. These water filters can use almost all 10" standard filter cartridges available on current market. The water filter comes with a quick-easy diverter valve to install the filter without extra fittings.

- **Ideal for a wide range of applications**
- **Available with clear Styrene-Acrylonitrile and opaque polypropylene**
- **Thicker walls for increased strenght**
- **Available port: 1/4", 1/2", 3/4", 1"**
- **Other color is optional**
- **Filter cartridge is optional**
- **With plastic bracket, wrench**

NW-BR10B1

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With plastic bracket, wrench, brass port

NW-BR10B2

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With plastic bracket, wrench, brass port

NW-BR10B

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With plastic bracket, wrench, brass port

NW-BR10B-PET

Inlet pressure:
8-300 psi/0,6-23 kg/cm^2

With plastic bracket, wrench, brass port

NW-BR10B3

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With plastic bracket, wrench, brass port

NW-BR10B4

Triple filtration
PP+GAC+CTO

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With steel bracket, wrench

NW-BR10B5

Triple filtration
PP+GAC+CTO

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm2

With steel bracket, wrench

NW-BR10A

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With plastic bracket, wrench, brass port

NW water filters

NW-BR10F2

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With plastic bracket, wrench, brass port

NW-BR10F

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With plastic bracket, wrench, brass port

NW-PRF02

Double filtration PP+CTO

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With steel bracket, wrench

NW-PRF03

Double filtration PP+UDF+CTO

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With steel bracket, wrench

NW-TRR01

Single filtration,
PP cartridge

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With a wrench, contains a diverter and a faucet

NW-TR201

Single filtration,
thread filter or PP cartridge

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With a wrench, contains a diverter and a faucet

NW-TR201-W

Single filtration,
thread filter or PP cartridge

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With a wrench, contains a diverter and a faucet

NW-TR202

Double filtration PP+CTO

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With a wrench, contains a diverter and a faucet

NW-TR203

Triple filtration
PP+GAC+CTO

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With a wrench, contains a diverter and a faucet

NW-TR203

Triple filtration
PP+GAC+CTO

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With a wrench, contains a diverter and a faucet

NW-PR202UV

Double filtration + UV light

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With steel bracket, wrench, faucet and other small accessories

NW-PR303A

Triple filtration
PP+CTO+T33

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With a wrench, faucet and other small accessories

NW water filters

NW-PR202

Double filtration PP+CTO

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With a wrench, faucet and other small accessories

NW-PR203

Triple filtration
PP+GAC+CTO

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With a wrench, faucet and other small accessories

NW-PR302

Double filtration PP+CTO

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With a wrench, faucet and other small accessories

NW-PR303

Triple filtration PP+GAC+CTO

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With a wrench, faucet and other small accessories

NW-PR304

4 stage filtration
PP+GAC+CTO+T33

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With a wrench, faucet and other small accessories

NW-PR305

5 stage filtration
PP+GAC+CTO+T33+T33

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With a wrench, faucet and other small accessories

NW-PR306

6 stage filtration

PP+GAC+CTO+T33+
T33+mineral filter

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With a wrench, faucet and other small accessories

NW-BRK01

Single filtration, PP filter cartridge

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With steel bracket, wrench

NW-BRK02

Double filtration PP+CTO or depend on your inquire

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With steel bracket, wrench

NW-BRK03

Triple filtration
PP+GAC+CTO or depend on your inquire

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With steel bracket, wrench

NW-BRKNW-BRL02-LS2

Double filtration PP+CTO or depend on your inquire

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With steel bracket, wrench

NW-BRM01

Single filtration, PP filter cartridge

Inlet pressure: 8-125 psi/0,6-8,8 kg/cm2

With steel bracket, wrench

NW water filters

NW-PR202

Double filtration PP+CTO

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With a wrench, faucet and other small accessories

NW-BRM03

Triple filtration PP+GAC+CTO or depend on your inquire

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With steel bracket, wrench

NW-BRM02-LS1

Double filtration PP+CTO or depend on your inquire

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With steel bracket, wrench

NW-BRL01

Single filtration, PP filter cartridge

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With steel bracket, wrench

NW-BRL02

Double filtration PP+CTO or depend on your inquire

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With steel bracket, wrench

NW-BRL03

Triple filtration PP+GAC+CTO or depend on your inquire

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With steel bracket, wrench

NW-BRL03-LS3

Double filtration PP+CTO or depend on your inquire

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With steel bracket, wrench

NW-PRG03YT

Triple filtratrion PP+GAC+CTO

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm^2

With a wrench, faucet and other small accessories

NW-PR203YT

Triple filtratrion PP+GAC+CTO

Inlet pressure:
8-125 psi/0,6-8,8 kg/cm2

With a wrench, faucet and other small accessories